

TECHNICAL DATA.

ECONOMY AND EMISSIONS		WLTP*
Energy consumption (weighted*, combined) with full battery	0.9 litres/100 km and 11.9 kWh/100 km	
Official CO ₂ emissions (weighted*, combined)	19 g/km	
Pure EV (electric-only) range	98 km	
Pure EV range (City)	122 km	
Range-extender range	391 km	
Total range	489 km	
Total range (City)	513 km	
Range-extender fuel economy	9.2 litres/100 km	

PERFORMANCE	
Acceleration	13.2 seconds (0-100 km/h)
Max. speed	128 km/h

WEIGHTS	
Kerb weight	Business: 2,070-2,201 kg City: 2,070-2,204 kg Ultima: 2,122-2,222 kg
Mass in running order**	Business: 2,165-2,296 kg City: 2,165-2,299 kg Ultima: 2,217-2,317 kg
Max. gross vehicle weight	2,900 kg
Max. gross train weight	2,900 kg
Max. technically permissible mass on front axle	1,500 kg
Max. technically permissible mass on rear axle	1,500 kg
Max. net payload***	Business: 604-735 kg City: 601-735 kg Ultima: 583-683 kg
Max gross payload***	Business: 699-830 kg City: 696-830 kg Ultima: 678-778 kg
Max. total on roof load - including roof system	100 kg

* Weighted values are mean values for fuel and electricity consumption of externally chargeable hybrid electric vehicles with an average usage profile and daily charging of the battery. The values were determined according to the more realistic test procedure WLTP (Worldwide harmonised Light vehicles Test Procedure), which replaces the test procedure with reference to the NEDC (New European Driving Cycle). All stated values are not part of the offer and may vary depending on driving style, loading, equipment, selected options and tyres.

**Unladen vehicle weight with driver (75 kg), determined in accordance with Regulation (EU) 1230/2012 in the currently applicable version, including fuel tank filled up to 90 % of capacity.

EXTERIOR DIMENSIONS	
Length	5,233 mm
Width (incl. mirrors)	2,083 mm
Width (excl. mirrors)	1,945 mm
Height (unladen)	1,990 mm
Height (fully laden)	1,932 mm
Wheelbase	3,386 mm
Front overhang	941 mm
Rear overhang	906 mm
Front track	1,622 mm
Rear track	1,637 mm
Min. ground clearance (fully loaded)	150 mm

LOADSPACE DIMENSIONS	
Length	2,447 mm
Load volume (liquid fill: behind bulkhead/max)	4.9 m ³ /5.5 m ³
Max. width	1,574 mm
Width between wheel arches	1,109 mm
Height	1,373 mm
Side load door entry width	938-1,128 mm
Side load door entry height	1,199 mm
Rear door entry width	1,253 mm
Rear load door entry height	1,272 mm
Rear loading height (step height from ground to load floor)	640 mm

DRIVE MOTOR	
Driven wheels	Rear
Peak power	110 kW
Peak torque	250 Nm
Max. rpm	11,500 rpm

***The payload includes the weight of the driver and passengers, luggage and all accessories.

Vehicle complies with the latest European Union emission regulations (Euro 6D).

DRIVE BATTERY

Drive battery type	3-string Lithium ion
Gross storage capacity	31kWh
Total number of cells	288

CHARGING

On-board charging AC	11 or 22 kW
On-board charging DC	50 kW
Optimum charging time @ 50 kW (0-100 %)	30 minutes
Optimum charging time @ 50 kW (0-80 %)	25 minutes
Optimum charging time @ 22 kW (0-100 %)	75 minutes
Optimum charging time @ 11 kW (0-100 %)	140 minutes
Optimum charging time @ 7 kW (0-100 %)	225 minutes

RANGE-EXTENDER

Fuel type	Petrol (95-RON up to E10)
Configuration	Inline 3 DOHC 12-valves
Induction	Direct injection, turbo-charged
Cubic capacity	1,477 cm ³
Power	67 kW
Electrical output	60 kW
Peak torque	160 Nm
Fuel tank capacity (usable)	38.5 (36) litres

BRAKES

Braking system	Front and rear floating caliper/ ventilated discs
Braking aids	ABS, Electronic Stability Control and Emergency Brake Assist

WHEELS & TYRES

Wheel size	7J X 17
Tyre size	215/60/R17 C 107 T
Rolling resistance	8,99 N/kN
Tyre Noise emissions	72 dB

STEERING

Power steering type	Electrical Hydraulic Power Assisted Steering (EHPS)
Steering ratio	15.2:1
Turning Circle (kerb to kerb)	10.1m
Turning Circle (wall to wall)	10.83m

WARRANTY

Standard vehicle warranty (distance)	240,000 km
Standard vehicle warranty (time)	5 years
Standard battery warranty (distance)	240,000 km
Standard battery warranty (time)	8 years

SERVICE INTERVAL

Service interval (distance)	40,000 km
Service interval (time)	1 year

SUSPENSION

Front	Dual-axis Macpherson strut/ anti-roll bar
Rear	Double-insulated 5-link with transverse composite leaf spring